

MUNCHKIN 199/399VWH HIGH EFFICIENCY HOT WATER SUPPLY BOILER

JOB NAME :
LOCATION :
ARCH./ENGR :
WHOLESALER :
MECH. CONTRACTOR :
MODEL NUMBER :
TYPE OF GAS :
BTU/HR INPUT LOW FIRE:
BTU/HR INPUT HIGH FIRE:
MODULATION RANGE (4:1 RATIO):

Standard Features

- 96% Efficiency
- Boiler bears the ASME "H" stamp
- Rated working pressure up to 125 PSI
- 125 PSI ASME Relief Valve
- Sealed Combustion Chamber
- Stainless Steel Premix " NIT " Burner
- Boiler Constructed of Stainless Steel
- Water Flow Switch
- Spark Ignition
- Flame Rectification Probe
- Stainless Steel Supply and Return Thermistors
- ASME Pressure Relief Valve (Rated at 125 PSI)
- High Limit Temperature Control with Manual reset
- Low NOx Operation exceeds most stringent Air Quality Requirements
- 24 Volt Transformer
- Modulating digital control system
- Digital Display Panel
- 5/8 Condensation Connection with Built-in Trap
- Electrical Junction Box with Switch
- Wiring Harness with Molex Connection
- Vent Termination Coupling and Tee (PVC)
- 5 Year Limited Warranty

Optional Equipment

- V1000** Aluminum Outside Termination Vent Kit for 199VWH
- V2000** Aluminum Outside Termination Vent Kit for 399VWH
- N1100** Condensation Neutralizer .

Additional Features

- Freeze Protection
- Adjustable differential
- Temperature measurement in Celsius or Fahrenheit
- Display will allow installer to check current status of the Munchkin parameters