

HP	Type	FLA	RPM	V	PH	HP	Type	FLA	RPM	V	PH	HP	Type	FLA	RPM	V	PH	
0.25	Open	5.1	1750	120	1	0.75	Open	1.0	1750	460	3	1.5	TEFC	2.7	1750	460	3	
		2.1	1750	208	1			0.7	1750	575	3			1.6	1750	575	3	
		2.3	1750	230	1			11.0	1750	120	1			16.4	1750	120	1	
		1.1	1750	208	3			6.3	1750	208	1			9.5	1750	208	1	
		1.4	1750	230	3			5.5	1750	240	1			8.2	1750	230	1	
		.75	1750	460	3			2.9	1750	208	3			4.3	1750	208	3	
0.25	TEFC	3.6	1750	120	1	0.75	TEFC	2.6	1750	240	3	2.0	Open	4.4	1750	230	3	
		2.2	1750	208	1			1.3	1750	460	3			2.2	1750	460	3	
		1.9	1750	230	1			11.0	1750	120	1			1.6	1750	575	3	
		1.6	1750	208	3			5.4	1750	208	1			20.4	1750	120	1	
		1.4	1750	230	3			5.5	1750	230	1			10.0	1750	208	1	
		0.7	1750	460	3			2.0	1750	208	3			10.2	1750	230	1	
0.33	Open	5.5	1750	120	1	1.0	Open	2.2	1750	230	3	2.0	TEFC	7.0	1750	208	3	
		3.2	1750	208	1			1.1	1750	460	3			6.6	1750	230	3	
		2.8	1750	230	1			0.8	1750	575	3			3.5	1750	460	3	
		1.4	1750	208	3			13.0	1750	120	1			2.1	1750	575	3	
		1.6	1750	230	3			7.5	1750	208	1			24.0	1750	120	1	
		0.8	1750	460	3			6.5	1750	240	1			12.0	1750	230	1	
0.33	TEFC	4.6	1750	120	1	1.0	TEFC	3.7	1750	208	3	3.0	Open	6.5	1750	208	3	
		2.3	1750	208	1			3.2	1750	240	3			5.8	1750	230	3	
		2.4	1750	230	1			1.6	1750	460	3			2.9	1750	460	3	
		1.2	1750	208	3			1.1	1750	575	3			2.3	1750	575	3	
		1.2	1750	230	3			13.0	1750	120	1			14.0	3600	208	1	
		0.6	1750	460	3			6.5	1750	230	1			12.4	3600	230	1	
0.50	Open	8.8	1750	120	1	1.5	Open	3.3	1750	208	3	3.0	TEFC	9.0	3600	208	3	
		5.1	1750	208	1			3.4	1750	230	3			8.6	3600	230	3	
		4.4	1750	230	1			1.7	1750	460	3			4.3	3600	460	3	
		3.0	1750	208	3			1.4	1750	575	3			3.6	3600	575	3	
		2.5	1750	230	3			15.0	1750	120	1			30.0	3600	120	1	
		1.0	1750	460	3			8.3	1750	208	1			15.0	3600	230	1	
0.50	TEFC	7.0	1750	120	1	1.5	TEFC	7.5	1750	230	1	3.0	TEFC	8.5	3600	208	3	
		3.4	1750	208	1			5.6	1750	208	3			8.2	3600	230	3	
		3.5	1750	230	1			5.0	1750	230	3			4.1	3600	460	3	
		2.3	1750	208	3									3.0	3600	575	3	
		2.3	1750	208	3													
		2.0	1750	230	3													